




# LINER

# Technical Datasheet

Material	Antistatic LDPE			
Antistatic treatment expiry date	1 year from production			
Shape	Donut with welded O-ring			
Lenght	From 5 m to 25 m (or customizable)			
Thickness	60µm	70µm	80µm	
	90µm	100µm	120µm	
Height	22cm	36cm	50cm	55cm
	70cm	80cm	90cm	100cm



The product is built in production rooms classified [ISO 8](#) according to UNI EN ISO 14644-1

The material used is compliant with the following standards, regulations and legislation:

- 👁️ [SUITABILITY FOR FOOD CONTACT](#) FDA requirements - Federal Code, Regulation 21 CFR)
- 👁️ [PHARMACEUTICAL AND BIOMEDICAL USE](#) EUROPEAN PHARMACOPEAS paragraph 3.1.3-4-5, USP paragraph 87, 88, 661 e 231
- 👁️ [ATEX REQUIREMENTS](#) Directive 2014/34/EU

Absence of:

- 👁️ [IMPURITIES AND CONTAMINANTS](#) EU Guideline EMA / CHMP / ICH / 353369/2013
- 👁️ [ALLERGENIC SUBSTANCES](#) Latex, Gluten, Melamine, Nitrocellulose and Amines
- 👁️ [MATERIALS OF ANIMAL ORIGIN \(BSE/TSE\)](#) Regulation 1069/2009 - EC and 142/2011 - EC in addition to the "Explanatory note EMEA/410/01,rev.3" about BSE / TSE (so-called "mad cow")
- 👁️ [PHTHALATES](#)
- 👁️ [NITROSAMINES](#)

